



DS77 series

Features Sony DepthSense TOF sensor


Class 1 Laser Product



机器视觉产业联盟
China Machine Vision Industry Union



3D Time-of-Flight Principle



A 3D time-of-flight sensor emits modulated infrared light outside the visible range. It is reflected by objects in its field of vision and then captured by the sensor. The time between the emission and reception of the reflected infrared light is called “time-of- flight” (ToF).

DS77 Series

SONY TOF Camera
Industrial Grade



EXW price:
DS77 Lite 599usd
DS77 Pro 699usd

[Specification Download](#)

Model	DS77 PRO	DS77 LITE
Back side		
Part No.	608000200022	608000200023
Sensor	Sony DepthSense ToF CMOS	
Illumination	940nm VCSEL * 2	
ToF Resolution/Frame rate	640*480, Max.25fps	
ToF HDR Mode	Supported with Max. 15fps	
ToF FOV	70°(H)*50°(V)	
Output Format	RAW12(Depth, IR)	
Interface	1000Mbps Ethernet and RS485	
Physical Connection	M12 Aviation Plug x 2	RJ45 x1 6pin Connector x 1
Power Supply	PoE+ or 12V~24V (DC)	12V~24V (DC)
Accuracy	<1%	
Working Range	0.15m to 5m	
Working Temperature	-20°C to +50°C	
Operation System & Platform	Windows/Linux/Arm Linux/ROS1/ROS2	
SDK	C/C++/Python/C#	
Enclosure Rating	IP67	IP42
Conformity	CE, FCC, FDA	

DS77C Series

SONY ToF + RGB Camera
Industrial Grade




EXW price:
DS77C Lite 749usd
DS77C Pro 849usd

[Specification Download](#)


Model	DS77C PRO	DS77C LITE
Back side		
Part No.	608000200022	608000200023
Sensor	Sony DepthSense ToF CMOS	
Illumination	940nm VCSEL * 2	
ToF Resolution/Frame rate	640*480, Max.25fps	
ToF HDR Mode	Supported with Max. 15fps	
ToF FOV	70°(H)*50°(V)	
RGB Camera	1600*1200, Global Shutter, 77°(H)*55°(V)	
Output Format	RAW12(Depth, IR) + JPG(RGB)	
Interface	1000M Ethernet and RS485	
Physical Connection	Aviation Plugs	RJ45 x1 6pin Connector x 1
Power Supply	12V~24V DC or PoE+	12V~24V DC
Accuracy	<1%	
Working Range	0.15m to 5m	
Working Temperature	-20°C to +50°C	
Operation System	Windows/Linux/Arm Linux/ROS1/ROS2	
SDK	C/C++/Python/C#	
Enclosure Rating	IP67	IP42
Conformity	CE, FCC, FDA	

Key Feature

- High accuracy and precision
- HDR mode supported to obtain data in high contrast, complex scenes
- Works well under bright sunshine or in dark scenes
- 2MP RGB resolution, Global shutter (for DS77C series)
- Matched depth image and RGB image (for DS77C series)
- IP67 and aviation plugs option selectable




[Click to download Point Cloud Data with HDR ON/OFF](#)



[Click to download Point Cloud Data with HDR ON/OFF](#)

FOV and Coverage



ToF FOV 70°(H)*50°(V)

$$Width = \tan\left(\frac{HFOV}{2}\right) * Distance * 2$$

$$Height = \tan\left(\frac{VFOV}{2}\right) * Distance * 2$$

Calculated detectable area from 1, 2, 3, 4meters away

Distance (meter)	Width (meter)	Height (meter)
1	1.4	0.93
2	2.8	1.86
3	4.2	2.8
4	5.6	3.73

You can also calculate Coverage by yourself:

<https://1drv.ms/x/s!Aq4U4G0CF3nCi3UX37hroT5w4ha-?e=n46lxr>

What's included in the SDK:


NebulaGUITool	With this application, users can quickly access DS77 series camera to view the stream of depth/IR, visualize point clouds, configure camera settings, upgrade firmware, etc. For models with RGB, users can also simultaneously access stream of RGB, IR, depth, mapped RGB and mapped depth.
Suite for OS and platforms	Different OS and platforms is supported like Windows, Ubuntu16/18/20, Arm Linux. The development suite includes dynamic libraries, C/C++ code samples, OPENCV samples, prebuilt bins.
Wrappers	Python API, as well as integration with the following 3rd-party technologies: ROS1 , ROS2 and more(C#, Halcon, GenICam) to come.
Code Samples	Code samples are included in every listed supported OS, platforms, and wrappers. These examples demonstrate how to easily use the SDK to include code snippets that access the camera into your applications. Check some of the C/C++ examples including point cloud capture and save, parameters setting and trigger mode setting, etc.

We constantly add new features to our SDK to expand the capabilities of your project. Click [NebulaSDK](#) to check detail or download.



A Glance of NebulaSDK

	AArch64	update ver 1.1.13
	Python	modify the VzDeviceInfo definition
	ROS/src/VzenseROS	modify README for ROS
	ROS2/src/VzenseROS	add ROS2
	Ubuntu16.04	update ver 1.1.13
	Ubuntu18.04	update ver 1.1.13
	Windows	fix error on windows x64
	LICENSE	fix error
	README.md	update ver 1.1.0









NebulaGUITool



DS77 Pro Dimension

[2D Drawing Download](#)

[3D .stp File Download](#)











DS77 Lite Dimension

[2D Drawing Download](#)

[3D .stp File Download](#)



- Sony ToF Sensor
- RGB + Depth
- Support PoE+



Focus on Industrial 3D Time-of-Flight Cameras







Letting Machines Perceive the 3D World

info@vzense.com
www.vzense.com

DS77C Pro Dimension

[2D Drawing Download](#)

[3D .stp File Download](#)











DS77C Lite Dimension

[2D Drawing Download](#)

[3D .stp File Download](#)



DS77C Pro/DS77 Pro Accessories included

Part No.	Description	Picture
814000304025	-CAT5e Ethernet Cable -Aviation Connector to RJ45 -Cord Length: 3m	
814000304026	-M12 Multiple Functional Cable -Cord Length: 2m	

DS77C Lite/DS77 Lite Accessories included

Part No.	Description	Picture
814000600015	-CAT5e Ethernet Cable -RJ45 to RJ45 -Cord Length: 3m	
814000300019	-DC 12~24V -Cord Length: 2m	
814000300014	-6pin Multiple Functional Cable -RS485, EXT IO -Cord Length: 1m	

Selectable Accessories

Lead Time: 2weeks

Item	Description	Picture	Price
1	-CAT5e Ethernet Cable -Aviation Connector to RJ45 -Cord Length: 5m		30usd
2	-CAT5e Ethernet Cable -Aviation Connector to RJ45 -Cord Length: 10m		45usd
3	-CAT5e Ethernet Cable -Aviation Connector to RJ45 -Cord Length: 20m		70usd
4	-CAT5e Ethernet Cable -Aviation Connector to RJ45 -Cord Length: 50m		95usd

Suggested PoE+ Injector

Supplier	Model
H3C	EWPAM2NPoE+
TP LINK	TL-PoE+170S

Vzense

ToF sensor & application



About Vzense Technology

Since 2016, Vzense Technology has been continuously pushing the boundaries of TOF sensor development and its application through the projects of global leading customers. Our team has 20+ years of experience in consumer electronics industry and supply chain management. Vzense successfully brought product quality, time of development, cost and advanced AI altogether into our creative products. We shipped over 100 thousand of products to big and small customers in 40+ countries. Our product development and supply chain is based in China and US, engineering service in China, US and EU, resellers in US, EU, and Japan.



机器视觉产业联盟
China Machine Vision Industry Union



Contact us



Website

Vzense USA
Newark, CA 94560

Vzense China
Suzhou and Qingdao, China

Email:

info@vzense.com

Phone:

+1(650)336-8158

Website:

vzense.com

SDK Download:

<https://github.com/vzense>

